# C-20-CPUSE-N-AI6

### 20 dB, Air Directional Coupler, 555-2700 MHz



#### **OBSOLETE**

This product was discontinued on: October 31, 2019

### **Product Classification**

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

N Female

Product Type Directional coupler

General Specifications

**Device Type** Coupler

**Application** Indoor/Outdoor

ColorSilverInner Contact PlatingSilver

Outer Contact Plating Trimetal

**Dimensions** 

Interface

 Height
 22 mm | 0.866 in

 Width
 75 mm | 2.953 in

 Length
 155 mm | 6.102 in

**Electrical Specifications** 

**3rd Order IMD** -160 dBc

3rd Order IMD Test MethodTwo +43 dBm carriersInsertion Loss at Frequency Band0.2 dB @ 555-2700 MHz

**Return Loss, minimum** 20.8 dB

COMMSC PE°

# C-20-CPUSE-N-AI6

Average Power, maximum 200 W

**Coupling** 20 dB

**Coupling Tolerance** ±1.0dB @ 698-2700 MHz | ±2.0dB @ 555-698 MHz

**Impedance** 50 ohm

**Isolation at Frequency Band** 40 dB @ 555-2700 MHz

**Operating Frequency Band** 555 – 2700 MHz

Peak Power, maximum 1 kW Reflected Power, maximum 200 W

**VSWR** 1.2

Mechanical Specifications

**Coupling Nut Proof Torque** 4.5 N-m | 39.828 in lb

### **Environmental Specifications**

**Operating Temperature**  $-35 \,^{\circ}\text{C} \text{ to } +85 \,^{\circ}\text{C} \, (-31 \,^{\circ}\text{F to } +185 \,^{\circ}\text{F})$ 

**Relative Humidity** Up to 100%

Ingress Protection Test Method IEC 60529:2001, IP65

Packaging and Weights

 Height, packed
 40 mm | 1.575 in

 Width, packed
 90 mm | 3.543 in

 Length, packed
 180 mm | 7.087 in

 Volume
 648 cc | 39.543 in³

 Weight, gross
 0.42 kg | 0.926 lb

 Weight, net
 0.38 kg | 0.838 lb

## Regulatory Compliance/Certifications

#### Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant





# C-20-CPUSE-N-AI6

