

C-6-UW-N-A16

6 dB, Air Directional Coupler, 555–6000 MHz



Product Classification

Regional Availability Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type Directional coupler

General Specifications

Device Type Coupler

Application Indoor/Outdoor

Color White

Inner Contact Plating Silver

Interface N Female

Outer Contact Plating Trimetal

Dimensions

Height 23 mm | 0.906 in

Width 70 mm | 2.756 in

Length 156 mm | 6.142 in

Electrical Specifications

3rd Order IMD -163 dBc

3rd Order IMD Test Method Two +43 dBm carriers

Insertion Loss at Frequency Band 1.8 dB @ 555–6000 MHz

Average Power, maximum 200 W

Coupling 6 dB

Coupling Tolerance ± 1.1 dB

Impedance 50 ohm

C-6-UW-N-A16

Isolation at Frequency Band	18 dB @ 4900–6000 MHz 22 dB @ 3800–4900 MHz 24 dB @ 2700–3800 MHz 26 dB @ 555–2700 MHz
Operating Frequency Band	555 – 6000 MHz
Peak Power, maximum	1 kW
Reflected Power, maximum	40 W
VSWR at Frequency Band	1.25:1 @ 2700–3800 MHz 1.2:1 @ 555–2700 MHz 1.3:1 @ 3800–6000 MHz

Mechanical Specifications

Coupling Nut Proof Torque	4.5 N-m 39.828 in lb
----------------------------------	------------------------

Environmental Specifications

Operating Temperature	-35 °C to +85 °C (-31 °F to +185 °F)
Relative Humidity	Up to 100%
Corrosion Test Method	IEC 60068-2-11, 30 days
Ingress Protection Test Method	IEC 60529:2001, IP67

Packaging and Weights

Height, packed	45 mm 1.772 in
Width, packed	98 mm 3.858 in
Length, packed	180 mm 7.087 in
Weight, gross	0.42 kg 0.926 lb
Weight, net	0.36 kg 0.794 lb

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

