

CHOOSE WELL...
CHOOSE WISELY...
CHOOSE MAXON...



LOOKING TO UPGRADE YOUR COMMUNICATION DEVICES FROM 2G TO 3G?

The Intelimax *Lite* is a cost effective serial modem ideal for high volume M2M applications. The essential features include Packet Switched Data, 2 way SMS, Circuit Switched Data and IP Stack, which makes the Intelimax *Lite* the perfect entry level communications device.

WANT MORE FEATURES?

The Intelimax delivers a superior communications solution to suit most industrial markets. The Intelimax combines the capability of a powerful onboard processor providing an innovative and comprehensive feature set. Enhanced capabilities include SSH, Telnet, Remote Management, onboard IP Stack and FTP.



Intelimax Lite Features




- Supports packet data and 2-way SMS
- RS232 Interface (RJ45 Connector)
- Auto recovery including detect and auto redial
- Wide ranging input voltage
- Remote AT Command configurable
- Windows GUI to access modem via IP Wan and serial port

Intelimax Features



All the features of the Intelimax Lite plus:

- Auto-Ping Timeout
- WAN Scheduling
- Supports SNMP, SSH, Sntp and Dynamic DNS
- Modem Emulation (CSD emulation in IP Mode)
- FTP Functionality



Windows Graphic User Interface

Applications



Remote Monitoring
Power and Substations



Monitor Security systems
and alarms



Data Logging



Weather Station



Fleet Management



Traffic Signals



3G Communications
Device



Metering



Frequency Bands

- WCDMA/HSDPA 850MHz, 900MHz, 1900MHz, 2100MHz
- GSM/GPRS/EDGE 850MHz, 900MHz, 1800MHz and 1900MHz



Metering



Water



Road Signs



Weather Stations



Transport



Power

Intelimax Lite General Features

- HSPA+/EDGE/GPRS/GSM module
- External antenna
- USB2.0 connection
- Packet switched data
- CSD (Circuit Switch Data)*
- 2x way SMS
- Remote SMS diagnostics
- Remote Telnet management
- Remote AT command configurable
- Remote /local user interface
- Extended AT command set
- External DC power
- Wide ranging input power
- Supports RS232
- Supports TCP/IP, UDP/IP Stack
- Supports Firmware over the AIR (FOTA)
- Auto recovery including detect and auto redial
- Inbuilt carrier detection watchdog
- Inbuilt periodic reset
- Diagnostic monitoring (Syslog)
- Backup configuration file (.dat)

*network dependant

Compliance

- RoHS Compliant
- ACMA

Connections

- RJ45 Connector for Serial communications (RS232) and Pin 1 for power
- 1 x mini USB connector
- 1 x SIM Card
- 1 x Antenna Connector FME Male
- Reset Button

Data

- HSPA+ (UL 5.6 Mbps , DL 21 Mbps)
- WCDMA PS: UL 384kbps/DL 3.6 Mbps
- WCDMA CS: UL 64kbps/DL 64kbps
- GPRS/EDGE: UL 59.2 Kbps / DL 236 Kbps
- GSM CS: UL 9.6kbps/DL 14.4kbps

Intelimax General Features

- HSPA+/EDGE/GPRS/GSM module
- External antenna
- USB2.0 connection
- Packet switched data
- CSD (Circuit Switch Data)*
- 2x way SMS
- Remote SMS diagnostics
- Remote SSH and Telnet management
- Remote AT command configurable
- Remote /local user interface
- Extended AT command set
- External DC power
- Wide ranging input power
- Supports DDNS
- Supports RS232
- Supports TCP/IP, UDP/IP Stack
- Supports Firmware over the AIR (FOTA)
- Onboard FTP Client
- Auto recovery including detect and auto redial
- Inbuilt carrier detection watchdog
- Inbuilt periodic reset
- Inbuilt WAN Scheduler
- Auto Ping watchdog
- Modem Emulator (CSD emulation in IP Mode)
- Diagnostic monitoring (Syslog)
- Backup configuration file (.dat)

*network dependant

Dimensions

71mm x 55mm x 26mm (without side brackets and antenna)

Environmental Specifications

- Operation Temperature -20 to 70° C
- Storage Temperature -40 to 85° C
- Humidity: 5%~ 95%

Power

- 6 - 32 V DC (reverse polarity protection)
- Active Mode 150mA @ 12V
- Dormant Mode 50mA @ 12V
- Sleep Mode 30mA @ 12V

Operating Systems for GUI use

- Microsoft Windows XP, 7, 8

